

BriskHeat® TOTE Wrap-Around Tote Tank / IBC Heater

Product Highlights

- ✓ Designed for caged, plastic, or metal tote tanks / IBCs
- ✓ Wrap-around blanket design allows you to heat a tote tank / IBC in a non-invasive way
- ✓ Does not contaminate or scorch your product unlike immersion heaters
- ✓ Two separate heat zones allow you to adjust heater output when content levels lower
- ✓ **CE** (see page A-2 for more information)

Configure-To-Order Option



Other Sizes, Shapes, Power

Temperatures up to




160°F (71°C)*

* Maximum content temperature may vary based on application (tote tank size, contents, etc).



Fits several tote tank sizes with adjustable nylon straps and buckles.



Includes standard plug for an easy electrical connection.



Controls temperature easily with adjustable thermostats.

Protects contents and tote tank surface from heat damage with manual reset high-limit safety thermostats.

Specifications:

- Full coverage plug-and-play system
- Fits any tote tank width from 40" x 40" (1016mm x 1016mm) to 48" x 48" (1219mm x 1219mm)
- Three standard height sizes: 36" (914mm), 42" (1067mm), 48" (1220mm)
- Two separate heat zones (top and bottom)
- Adjustable thermostat: 50-160°F (10-71°C)
- Built-in manual reset high-limit safety thermostat set at 195°F (91°C) for each heat zone
- Attachment method: adjustable nylon straps with buckles (Two across the top and three around the tank)**
- Silicone impregnated cloth facing and liner
- 1/4" (6mm) fiberglass insulation
- "Mouse hole" designed for spigot
- Patented ground for your safety
- 120 / 240VAC
- Total wattage: 120VAC = 1440 watts
240VAC = 2880 watts
- Power cord 6 feet (1.8M) long with standard power plug:
120VAC = NEMA 5-15
240VAC = NEMA 6-15
- Optional insulated top cover [reduces heat loss and accelerates heat-up]

** A hook and loop fastener like VELCRO® may be used for exact fitting configure-to-order models

Ordering Information:

Height in (mm)	Total Wattage 120V / 240V	Weight lb (kg)	Part Number 120VAC	Part Number 240VAC
36" (914)	1440 / 2880	34 (15)	TOTE361-ADJ	TOTE362-ADJ
42" (1067)	1440 / 2880	40 (18)	TOTE421-ADJ	TOTE422-ADJ
48" (1220)	1440 / 2880	46 (21)	TOTE481-ADJ	TOTE482-ADJ

Accessories:

Part Number	Description
TOTE-TOP	Insulated top cover

240VAC model is strongly recommended for applications that involve heat-up and melting due to the higher wattage.